

SPECIFIC NOTES:-

COPYRIGHT:-

9. M8 BOLTS TO BE TIGHTENED TO 21.0Nm ± 2.0 Nm 8. M6 BOLTS TO BE TIGHTENED TO 9.0Nm ±1.0Nm 7. M5 BOLTS TO BE TIGHTENED TO 5.0Nm ±1.0Nm 6. M4 BOLTS TO BE TIGHTENED TO 2.5Nm ±0.5Nm 5. ALL ANGULAR DIMENSIONS TO BE ±0.5° UNLESS OTHERWISE SPECIFIED 4. GENERAL TOLERANCE OF +0.1/-0.0 FOR DRILL HOLES UNLESS STATED OTHERWISE 3. REMOVE ALL BURRS AND SHARP EDGES 2. GENERAL TOLERANCE OF ±0.2mm UNLESS STATED OTHERWISE 1. ALL DIMENSIONS IN MM UNLESS STATED OTHERWISE 10. M10 BOLTS TO BE TIGHTENED TO 43.0Nm ±3.0Nm

GUARDRAIL ENGUARD KICKBACK, STBD

LEWMAR

LEWALAR STEERING DIVISION
UNT 1, BLOCK B. PORTRIWKY, LAPORTE WAY,
ULTON, BEDFRODSHRE, UK. LLA, BET
ALL: +44(0) 1582 404400 FAX: +44(0) 1582 404031
BLAL: DESSAMMHITLOCKSTEERING.COM

ARTHUR T 06/10/2003 1 OF 1 1:5 @ A3 85000397

DWG NO:-D 89

89400033