

Kättingguide																													
		6 mm DIN 766	6 mm ISO 4565	1/4" ACCO ISO G43 (G4)	7mm DIN 766	1/4" ACCO BBB (3B)	8mm DIN 766	8mm ISO 4565	5/16" ACCO ISO G43 (G4)	LEWMAR 9.5mm G40	3/8" CAMPBELL S4	10mm ISO 4565	3/8" CAMPBELL S3	10mm DIN 766	3/8" ACCO ISO G43 (G4)	11mm SHORT LINK	11mm DIN766	7/16" ACCO ISO G43 (G4)	LEWMAR 12mm G30/G40 12mm SHORT LINK	13mm DIN 766	1/2" ACCO ISO G43 (G4)	LEWMAR 14mm G30/G40 14 mm SHORT LINK	14mm DIN 766	14mm STUDLINK	16mm SHORT LINK	16mm DIN 766			
<b>D</b>	mm	6	6	7	7	7.14	8	8	8.4	9.5	10	10	10	10	10	11	11	11.8	12	13	13.2	14	14	14	14	16	16		
	inch	0.236	0.236	0.276	0.276	0.281	0.315	0.315	0.329	0.374	0.39	0.394	0.37	0.394	0.394	0.433	0.433	0.464	0.472	0.512	0.520	0.551	0.551	0.551	0.630	0.630			
<b>P</b>	mm	18.5	18	21.3	22	22.1	24	24	26.2	31.5	29	30	35	28	31	33	31	35.5	36	36	40.4	42	41	56	48	45			
	inch	0.728	0.709	0.840	0.866	0.870	0.945	0.945	1.030	1.240	1.15	1.181	1.36	1.102	1.220	1.299	1.22	1.4	1.417	1.417	1.591	1.654	1.614	2.205	1.890	1.772			
<b>W</b>	mm	20.4	21.6	24.4	23.8	25.2	27.2	28.8	29.7	31.6	35	36	34	36	35	39	40	40.1	40.5	47	45.7	49	50	50.4	56	58			
	inch	0.803	0.85	0.962	0.937	0.992	1.07	1.134	1.168	1.244	1.3	1.417	1.31	1.417	1.378	1.535	1.575	1.578	1.594	1.850	1.799	1.929	1.969	1.984	2.205	2.283			

