

GT SERIES - LED

37146 Old Hwy 17 - Culbertson, NE 69040 | 800.557.0098 | golight.com



PERMANENT MOUNT

Wireless Hand-Held Remote
20004GT (white) 20514GT (black)

Hard-Wired Dash Mount Remote
20204GT (white) 20214GT (black)

Wireless Hand-Held &
Wireless Dash-Mount Remotes
20074GT (white) 20574GT (black)

PORTABLE MODELS


Permanent Shoe
Wireless Remote - 79004GT (white)

PORTABLE MODELS

Magnetic Shoe
Wireless Hand-Held Remote
79014GT (white) 79514GT (black)



Golight RadioRay LED Light Beam Dimensions



Illuminance (Lux) 656 164 41 10

Peak Beam Intensity: 410,000 Candela
Maximum Beam Distance: 1,280 m / 4,200 ft
Beam Angle: 8°



Housing:	Heat resistant and high impact injection molded housing ASA Polymer (white housing) ABS Polymer (black housing)
Ingress Protection:	IP 56
Parts:	Nylon, Acetal Rack O-ring, Stainless Steel pinion drive 15' 18G cord with universal cigarette lighter plug
Fasteners:	Stainless Steel
Motors:	Automotive grade 12V D.C. Stall Torque 15.6 kg-cm No-load Speed 55.8 rpm Rated Output Power 1.42 W Stall Protected
Quality and Type of LED's:	10 High Flux LED's P-Vex lens technology 8° beam angle Anodized Aluminum heat sink w/liquid powder-cast finish
Peak Beam Intensity:	410,000 Candela
Max Beam Distance:	4,200 ft
Voltage DC:	12V
Power Consumption:	40W
Max Current Draw:	3 amps
Wireless Remote Control:	Radio Frequency: 433 MHz > 2000 possible address codes with 7 station dip switch Transmitter power: 2 Duracell MN21 12v batteries Radio Frequency allows for remote operation up to 80 feet away
Hardwired Dash Mount Remote:	On/Off switch, 4 way toggle 20' of six wire cord
Warranty:	3 Year Limited Warranty
Mounting Options:	Permanent Mount, Portable Light/Magnetic Shoe, Portable Light/Permanent Shoe
Rockguard:	Not Available for LED Models