Styker ST Series - Halogen

37146 Old Hwy 17 - Culbertson, NE 69040 | 800.557.0098 | golight.com




PERMANENT MOUNT MODELS Wireless Hand-Held Remote 3000ST (white) 3006ST (chrome) 3051ST (black)

PORTABLE MODELS (Magnetic Base) Wireless Hand-Held Remote 30002ST (white) 30062ST (chrome) 30512ST (black)



Light Beam Dimensions



Illuminance (Lux) 360 90 25 6 Peak Beam Intensity: 225,000 Candela Maximum Beam Distance: 949 m / 3,113 ft Beam Angle: 8°

-





Housing:	ASA Luranheat resistant
	High Impact, UV resistant material
Gears & Transmission Parts:	Lexan and Brass
Fasteners:	Stainless Steel
Motors:	Automotive grade 12V D.C. High Torque, R.P.M. 6087
	Constant Torque 17.133 mN.m/amp, Stall: 12.31 mN.m Draw point 4 amps
	Output: 1.96 watts w/built in stall protection circuitry
	Built in stall protection circuitry
Lamp / Cr5 II Pentabeam :	Phillips H9 (Bulb (est. 270 life hours)
Peak Beam Intensity:	225,000 Candela
Max Beam Distance:	3,113 ft.
Reflector:	Computer generated parabolic
Voltage DC:	12V
Power Consumption:	65W
Max current draw:	5.5 amps
Wireless Remote Controls:	Radio Frequency: 2.4 GHz
	Code match pairing process
	Batteries: 2 AAA
Warranty:	5 Year Limited Warranty
Mounting Options:	Permanent Mount or Portable Magnetic Base
Rockguard:	Included with all Halogen Styker Models