Stryker ST Series - LED

37146 Old Hwy 17 - Culbertson, NE 69024 | 800.557.0098 | golight.com





PERMANENT MOUNT MODELS


Wireless Hand-Held Remote 30004ST (white) 30064ST (chrome) 30514ST (black)

PORTABLE MODELS Magnetic Base

Wireless Hand-Held Remote 30005ST (white) 30065ST (chrome) 30515ST (black)



Light Beam Dimensions



Illuminance (Lux) 656 164 41 10 Peak Beam Intensity: 410,000 Candela Maximum Beam Distance: 1,280 m / 4,200 ft

Beam Angle: 8°















Housing:	ASA Luran heat resistant
	High impact, UV resistant material
Gears &Transmission Parts:	Lexan and Brass
Fasteners:	Stainless Steel
Motors:	Automotive grade 12V D.C. High Torque, R.P.M. 6087
	Constant Torque 17.133 mN.m/amp, Stall:12.31 mN.m Draw point 4 amps
	Output: 1.96 watts w/built in stall protection circuitry
	Built in stall protection circuitry
Type and Quality of LED's:	10 High Flux LED's
	P-Vex lens technology
	8° beam angle
	Anodized Aluminum heat sink w/liquid powder-cast finish
Peak Beam Intensity:	410,000 Candela
Max Beam Distance:	4,200 ft.
Voltage DC:	12V
Power Consumption:	40W
Max Current draw:	3.5 amps
Wireless Remote Controls:	Radio Frequency: 433 MHz
	Code match pairing process
	Batteries: 2 AAA
Warranty:	5 Year Limited Warranty
Mounting Options:	Permanent Mount
	or Portable Magnetic Base